

SMMSi / SHRMi VRF Indoor Unit MMC-AP0421H2UL - Underceiling

TOSHIBA
Carrier

Submittal Data

Job Data _____ Location _____
 Buyer _____ Buyer PO # _____ Carrier # _____
 Unit Number _____ Model Number _____
 Performance Data Certified By _____ Date _____



SMMSi / SHRMi VRF Underceiling Features

- R-410A Refrigerant
- Four sizes from 18,000 to 42,000 Btu/h
- Quiet operation, as low as 32.5 dBA
- Vertical airflow can be set to swing or fixed position
- Auto or manually set three fan speeds
- Easy to remove cleanable filter
- Five-year parts limited warranty

Indoor Unit Model	MMC-AP0361H2UL	
PERFORMANCE		
Cooling Rated Capacity	Btu/h	42,000
Heating Rated Capacity	Btu/h	47,500
Fan Type (Qty)		Centrifugal (4)
Airflow (L / M / H)	CFM	730 / 820 / 950
Sound Pressure (L / M / H)	dBA	39.5 / 42.5 / 46
ELECTRICAL		
Power Supply	V/Ph/Hz	208-230/1/60
Power Consumption (Input)	kW	0.11
Full Load Amps (FLA)	A	0.9
Minimum Circuit Amps (MCA)	A	1.2
Maximum Overcurrent Protection (MOCP)	A	15
Motor Type	DC Inverter Driven	
Motor Watts		120

PHYSICAL DATA

Pipe Connection Size - Liquid (High Pressure)	in.	3/8 (Flare)
Pipe Connection Size - Gas (Low Pressure)	in.	5/8 (Flare)
Pipe Connection Size - Drain (OD)	in.	1
Pipe Connection Size - Drain (ID)	in.	13/16
Refrigerant	R-410A	
External Finish	Munsell 10Y9.3/0.4	
Unit Width	in.	62-3/4
Unit Height	in.	8-5/16
Unit Depth	in.	26-3/4
Unit Net Weight	lb	75

ACCESSORIES (Optional)

- Lite Vision Plus Remote Controller (7-Day Programmable) RBC-AMS51E-ES
- Simple Wired Remote Control RBC-AS41UL
- Stand-Alone Receiver with Wireless Remote TCB-AX32UL
- Integral Receiver with Wireless Remote RBC-AX33CUL
- Remote Sensor TCB-TC41LUL
- Wired Remote Controller RBC-AMT32UL
- Elbow Piping Kit TCB-KP22CUL
- Condensate Drain Pump Kit TCB-DP22CUL

Manufacturer reserves the right to discontinue, or change at any time, specifications or designs without notice and without incurring obligations.

DIMENSIONAL DRAWING INDOOR UNIT UNDERCEILING MMC-AP0421H2UL

